

Multi-Tool

to fit 30mm exit shaft (Full Pack; options 1 - 2)

Stock Code: **MT- HH/30**

Shaft Size: **30mm Exit Shaft**
Outer Diameter: **46mm**

SETTINGS



2 x Cutting Knives (CK-HH/30-1):

(48.85mm Outer Diameter) used for trimming on normal stock

Kiss-Cutting Blade (CK-HH/30-2):

(46.35mm Outer Diameter **optional**) used for kiss-cutting applications

Long Cutting Knives (CK-HH/30-3):

(52mm Outer Diameter **optional**) used for trimming on heavy stock

2 x Black Gripper Band (M-76):

used to feed and support material through device

2 x Blue Gripper Band (M-83):

used to feed and support material through device during edge trimming only

Additional Information

Compatible on:

Perforating Blades:

17 TPI (MPB-17-HH/30MM) (250/280-350gsm)

Blue Nylon Sleeve

17 TPI (MPB-17-HH/30MM) (170-250/280gsm)

Black Nylon Sleeve

25 TPI (MPB-25-HH/30MM) (100-170gsm)

Black Nylon Sleeve

52 TPI (MPB-52-HH/30MM) (65-100gsm)

Black Nylon Sleeve

Contents of Package

1x Male Blade Holder (MT-BH-HH/30):

used to hold the perforating blade whilst material is fed through

1x Female Nylon Sleeve Holder (MT-NSH-HH/30):

used to secure nylon during perforating and kiss-cutting process

1x Black Nylon Sleeve (MT-NY/SL-HH-30):

used on light weight stocks (65-250/280gsm), allow sufficient blade pressure onto material (for perforating and kiss-cutting only)

1x Blue Nylon Sleeve (MT-NY/SL-HH-30-B):

used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

2 x Cutting Bosses (CB-HH-01):

used to aid cutting, producing scissor effect as material is fed through device (for slitting only)

1 x Waste Stripper (TWS-ID/MBO30-5):

acts as waste deflector preventing waste material wrapping around machine shaft; width options include:

5mm Width (TWS-ID/MBO30-5)

4mm Width (TWS-ID/MBO30-4) **optional**

3mm Width (TWS-ID/MBO30-3) **optional**

1 x Extraction Tool:

used to change rubber grippers from Male Blade Holder



Tech 184 (Blade Holder) and 185 (Nylon Sleeve Holder)