Multi-Tool

to fit 35mm exit shaft (Full Pack; options 1 - 2)

Stock Code: MT- HH/35

SETTINGS



Additional Information

Compatible on:

Contents of Package

1x Male Blade Holder (MT-BH-HH/35):

used to hold the perforating blade whilst material is fed through

1x Female Nylon Sleeve Holder (MT-NSH-HH/35):

used to secure nylon during perforating and kisscutting process

1x Black Nylon Sleeve (MT-NY/SL-HH-35):

used on light weight stocks (65-250/280gsm), allow sufficient blade pressure onto material (for perforating and kiss-cutting only)

1x Blue Nylon Sleeve (MT-NY/SL-HH-35-B):

used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

2 x Cutting Bosses (CB-HH-01):

used to aid cutting, producing scissor effect as material is fed through device (for slitting only)

Outer Diameter: 58.25mm

Shaft Size: 35mm Exit Shaft

2 x Cutting Knives (CK-01):

(62.50mm Outer Diameter) used for trimming on normal stock

Kiss-Cutting Blade (CK-02):

(58.35mm Outer Diameter **optional**) used for kiss-cutting applications

Long Cutting Knives (CK-03):

(64mm Outer Diameter **optional**) used for trimming on heavy stock

2 x Black Gripper Band (M-15):

used to feed and support material through device

2 x Blue Gripper Band (M-40):

used to feed and support material through device during edge trimming only

Perforating Blades:

17 TPI (MPB-17) (250/280-350gsm)

Blue Nylon Sleeve

17 TPI (MPB-17) (170-250/280gsm)

Black Nylon Sleeve

25 TPI (MPB-25) (100-170gsm)

Black Nylon Sleeve

52 TPI (MPB-52) (65-100gsm)

Black Nylon Sleeve

12 TPI (MPB-12) (optional)

72 TPI (MPB-72) (optional)

1 x Waste Stripper (TWS-ID/35-5):

acts as waste deflector preventing waste material wrapping around machine shaft; width options include:

5mm Width (TWS-ID/35-5)

4mm Width (TWS-ID/35-4) optional

3mm Width (TWS-ID/35-3) optional

1 x Extraction Tool:

used to change rubber grippers from Male Blade Holder



Tech 160 (Blade Holder) and 161 (Nylon Sleeve Holder)