# **Multi-Tool**

to fit 35mm exit shaft (Full Pack; options 1 - 2)

Stock Code: MT-SH/65

# **SETTINGS**



#### Additional Information

## Compatible on:

# **Contents of Package**

# 1x Male Blade Holder (MT-BH-SH/65):

used to hold the perforating blade whilst material is fed through

# 2x Female Nylon Sleeve Holders (CP-AP-NSH-SH/65):

used to secure nylon during perforating and kisscutting process

#### 1x Black Nylon Sleeve (CP-NY/SL-SH-65):

used on light weight stocks (65-250/280gsm), allow sufficient blade pressure onto material (for perforating and kiss-cutting only)

#### 1x Blue Nylon Sleeve (CP-NY/SL-SH-65-B):

used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

# 2 x Cutting Bosses (CB-SH/65-01):

used to aid cutting, producing scissor effect as material is fed through device (for slitting only)

# 2 x Cutting Knives (CK-SH/65-01):

(69.50mm Outer Diameter) used for trimming on normal stock

Shaft Size: 35mm Exit Shaft
Outer Diameter: 65mm

# Long Cutting Knives (CK-SH/65-02):

(71.00mm Outer Diameter **optional**) used for trimming on heavy stock

## 2 x Black Gripper Band (M-59):

used to feed and support material through device

#### 2 x Blue Gripper Band (M-148):

used to feed and support material through device during edge trimming only

#### **Perforating Blades:**

17 TPI (MPB-17/SH-65) (250/280-350gsm)

**Blue Nylon Sleeve** 

17 TPI (MPB-17/SH-65) (170-250/280gsm)

Black Nylon Sleeve

25 TPI (MPB-25/SH-65) (100-170gsm)

Black Nylon Sleeve

52 TPI (MPB-52/SH-65) (65-100gsm)

Black Nylon Sleeve

#### 1 x Waste Stripper (TWS-ID/35-5):

acts as waste deflector preventing waste material wrapping around machine shaft; width options include:

5mm Width (TWS-ID/35-5)

4mm Width (TWS-ID/35-4) optional

3mm Width (TWS-ID/35-3) optional

#### 1 x Extraction Tool:

used to change rubber grippers from Male Blade Holder



Tech 307 (Blade Holder) and 309 (Nylon Sleeve Holder)