

# Multi-Tool

to fit 20mm exit shaft (Micro-perforating/Kiss-cutting; option1)

Stock Code: **MT-MB OPTION 1**

Shaft Size: **20mm Exit Shaft**  
Outer Diameter: **40mm**

## SETTINGS



## Additional Information

Compatible on:

**TA 52**

(computerized buckle plate adjustment)

## Contents of Package

**1x Male Blade Holder (MT-BH/MB-20):**  
used to hold the perforating/slitting blade whilst material is fed through

**1 x Female Nylon Sleeve Holder (MT-NSH/MB/20):**  
used to secure nylon perforating and kiss-cutting process

**1x Black Nylon Sleeve (MT-NY/SL-MB):**  
used on light weight stocks (65-250/ 280gsm), to allow sufficient blade pressure onto material (for perforating and kiss-cutting only)

**1x Blue Nylon Sleeve (MT-NY/SL-MB-B):**  
used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

**Kiss-Cutting Blade (CK-MB-02):**  
(40.35mm Outer Diameter **optional**) used for kiss-cutting applications

## Perforating Blades:

17 TPI (**MPB-MB-17**) (250/280-350 gsm)

**Blue Nylon Sleeve**

17 TPI (**MPB-MB-17**) (170-250/280 gsm)

**Black Nylon Sleeve**

25 TPI (**MPB-MB-25**) (100-170 gsm)

**Black Nylon Sleeve**

52 TPI (**MPB-MB-52**) (65-100 gsm)

**Black Nylon Sleeve**

72 TPI (**MPB-MB-72**) (optional)

## 2 x Perforator Blade Seals (M-32):

## 2 x Black Gripper Bands (M-55):

used to feed and support material through device



Tech 142 (Blade Holder) Tech 143 (Nylon Sleeve Holder)